



Flange Units

UCFA 2 (normal-duty)



Unit No.	Shaft Dia		Dimensions (in./mm)											Bolt Used		Bearing No.	Housing No.	Weight kg.
	d (in.)	d (mm)	a	e	f	g	l	s	b	Z	c	Bi	a	(mm)	(in.)			
UCFA 201 201-8	1/2	12	3 7/32	3 3/4	3 5/4	7/16	1 5/16	3 3/4	2 1/16	1 1/4	1 13/32	1.2205	0.5000	8	5/16	UC 201 201-8	FA 204	0.47
UCFA 202 202-10	5/8	15	3 7/32	3 3/4	3 5/4	7/16	1 5/16	3 3/4	2 5/16	1 1/4	1 13/32	1.2205	0.5000	8	5/16	UC 202 202-10	FA 204	0.47
UCFA 203		17	3 7/32	3 3/4	3 5/4	7/16	1 5/16	3 3/4	2 5/16	1 1/4	1 13/32	1.2205	0.5000	8	5/16	UC 203	FA 204	0.47
UCFA 204-12 204-12	3/4	20	3 7/32	3 3/4	3 5/4	7/16	1 5/16	3 3/4	2 5/16	1 1/4	1 13/32	1.2205	0.5000	8	5/16	UC 204-12 204-12	FA 204	0.47
UCFA 205-14 205-15 205 205-16	7/8 1 1/16 1 1	25	4 7/8	3 3/4	5/8	1/2	1 1/16	7/16	2 3/4	1 13/32	2 17/32	1.3386	0.5630	10	3/8	UC 205-14 205-15 205 205-16	FA 205	0.68
UCFA 206-18 206 206-19	1 1/8 1 1/8 1 3/16	30	5 9/16	4 3/4	5/8	1/2	1 1/16	7/16	3 3/16	1 9/16	2 1/16	1.5000	0.6260	10	3/8	UC 206-18 206 206-19	FA 206	1.0
UCFA 207-20 207-21 207-22 207 207-23	1 1/4 1 1/4 1 3/8 1 3/8 1 7/16	35	6 3/16	5 1/8	5/8	9/16	1 1/16	7/16	3 3/16	1 3/8	2 19/32	1.6890	0.6890	12	7/16	UC 207-20 207-21 207-22 207 207-23	FA 207	1.5
UCFA 208-24 208-25 208	1 1/2 1 1/2 1 1/2	40	6 23/32	5 3/4	5/8	9/16	1 1/2	7/16	4 1/8	2	3 9/16	1.9370	0.7480	12	7/16	UC 208-24 208-25 208	FA 208	1.9
UCFA 209-26 209-27 209-28 209	1 5/8 1 13/16 1 3/4 1 3/4	45	7 1/16	5 3/4	5/8	9/16	1 1/16	1 13/32	4 3/8	2 1/16	3 3/16	1.9370	0.7480	14	1/2	UC 209-26 209-27 209-28 209	FA 209	1.7
UCFA 210-30 210-31 210	1 7/8 1 13/16 1 7/8	50	7 7/16	6 3/4	5/8	9/16	1 1/16	1 13/32	4 9/16	2 3/16	3 5/8	2.0315	0.7480	14	1/2	UC 210-30 210-31 210	FA 210	2.0
UCFA 211-32 211-34 211 211-35	2 2 1/8 2 2 3/8	55	8 1/2	7 1/4	1 1/4	1 1/2	1 13/32	5/8	5 1/4	2 5/8	4 1/2	2.1890	0.8740	15	9/16	UC 211-32 211-34 211 211-35	FA 211	3.6